



Byretech Ltd

The Bathroom Water Damage Prevention Specialists

Unit 51 Padgets Lane
South Moons Moat
Redditch, Worcs,
England B980RD

Tel: 01527 522 522
Fax: 01527 522 111
www.byretech.com
sales@byretech.com

Technical Data Sheet for High Performance FR / HD Shower Curtain Fabric

Composition	100% Polyester impregnated / coated with Microporous non water based polymer coating giving flame retardant properties.
Flame Retardant	BS 5867 Part 2 Type B
Shower / Waterproof	Hydrostatic head BS3424 30cm (will hold 30cm column of water) No penetration or absorption of water or oil based solutions.
Antibacterial	Will not support microbial growth including e-coli and M.R.S.A.
Antifungal	Will not support the growth of Mildew or any other fungal growth.
Stain Resistant	Good quality stain removal has been observed for the following: Blood, Urine, Grease, Ink, Coffee, Grape Juice, Iodine, Betadine, Ketchup, Mustard, Salad Dressing, Suntan Lotion etc.
Material Care	<p>Routine soap and water sponging is effective against ordinary soiling.</p> <p>Please note the material can be washed in a washing machine at 30 Deg C with normal washing detergent products. Washing at higher temperatures will damage / delaminate the coating.</p> <p>Fresh stains can be removed with standard bathroom water based spray cleaning agents or a sponge with a mild detergent applied and then rinsed down immediately afterwards.</p> <p>The curtain should then be allowed to dry out naturally.</p> <p>Maintaining the curtains life and cleanliness can be enhanced by rinsing the curtain after showering, thus removing the soap / conditioner / body wash and deposited skin cells from the material.</p>
Weight	120g per sq metre Available in white only

Note.

The data provided above is accurate at the time of receiving the first batch of material along with the test certification confirming the FR nature of the product then being produced into shower curtains for domestic / commercial use.

Byretech cannot be held responsible for misuse of the end product in any way and our liability is as per the products 1 year guarantee against faulty workmanship.

Byretech – 2021 – All rights reserved.